9.7 R6: Lakeshore Residential

9.7.1 Purpose

The purpose is to provide a **zone** for the **development** of residential housing along the lakefront in the form of **single detached**, **semi-detached** or **duplex housing**. The R6c sub-zoning district allows for **care centre**, **major** as an additional use. The R6h sub-zoning district allows for **home based business**, **major** as an additional use. (Bylaw 5467)

9.7.2 Primary Uses

- care centre, major (use is only permitted with the R6c sub-zoning district)
- duplex housing
- semi-detached housing
- single detached housing

9.7.3 Secondary Uses

- accessory dwellings (Bylaw 5978)
- bed and breakfast homes (in single detached housing or semi-detached housing or duplex housing only) (Bylaw 5498)
- boarding rooms
- care centre, minor
- docks, private
- home based businesses, minor
- home based businesses, major (in single detached housing only) (use is only permitted with R6h sub-zoning district)
- secondary suites (Bylaw 5969)

9.7.4 Subdivision Regulations

- Minimum lot width is 18.0m, except it is 20.0m for a corner lot. In the case of an irregular lot or panhandle-shaped lot, the minimum lot width shall be determined as described in the respective definitions of a panhandle lot and irregular-shaped lot.
- Minimum lot area is 560m² with one dwelling or 1120m² with two dwellings. The minimum lot area is 10,000m² if the lot is not serviced by a community sewer system.

9.7.5 Party Wall Subdivision Regulations

Lot Type	Minimum Lot area		Minimum Lot Width	
	Interior	corner	interior	corner
Semi-Detached Housing	560m²	600m²	9.0m	10.0m

9.7.6 Development Regulations

- Maximum site coverage is 40% and together with driveways, parking areas and impermeable surfaces shall not exceed 50%.
- Maximum density of dwelling units connected to a community sewer system shall be 1 dwelling unit per 560 sq. m. of lot area.
- Maximum density of dwelling units connected to a septic sewer system shall be 1 dwelling unit per 10,000 sq. m. (1ha) of lot area.

- Maximum height is 10.0m, except it is 4.5m for secondary buildings and secondary structures.
- Minimum front yard is 4.0m and it is 6.0m from a garage or carport to the back of curb or sidewalk for vehicular entry, or it is 2.6m to the side of the garage and front façade for side-entry garage and driveway layouts.
- Minimum side yard is 1.5m, except it is 4.0m from a flanking street. Where there is no direct vehicular access to the rear yard or to an attached garage or carport, one side yard shall be at least 3.0m. The minimum side yard setback for shared interior party walls shall be 0.0m.
- Minimum rear yard is 7.5m, except it is 1.0m for secondary buildings. Where the lot width exceeds the lot depth, the minimum rear yard is 4.5m provided that one side yard shall have a minimum width of 4.5m.
- The maximum height of any vertical wall element facing a front, flanking or rear yard (including walkout basements) is 6.5m, above which the building must be set back at least 1.2m.

9.7.7 Other Regulations

- In order for bareland strata development to be consistent with the character of the surrounding neighborhood, the strata plan shall be considered as one site for defining the overall use, density and site coverage.
- Minimum 7.5m horizontal setback of any building from the natural boundary.
- There shall be no more than two dwelling units per lot.
- Development Permit approval of a secondary suite on a lot not connected to a community sewer system is subject to the verification by the City's Engineering Department of sufficient septic tank or Engineered Secondary Sanitary Treatment Process capacity and approval by the Health Authority.
- A minimum area of 25m² of private open space shall be provided per dwelling.
- In addition to the regulations listed above, other regulations may apply. These include the general **development** regulations of Section 4 (secondary **development**, **yards**, projections into **yards**, lighting, agricultural setbacks, etc.); the specific use regulations of Section 5; the **landscaping** and fencing provisions of Section 6; and, the parking and loading regulations of Section 7.
- As per Section 4.10.2 All buildings and structures, excluding perimeter fencing (garden walls and fences) on lots abutting City Roads as identified on Schedule "B" shall not be sited closer to the City Road than the setback as per the appropriate zone measured from the offset Rights of Way as illustrated on Schedule "B". (Bylaw 5440)